

a message to our industry from ...

Electric Machinery Committee Task Force

Robert Thornton-Jones John Yagielski Lon Montgomery




Brush Electrical Machines GE Power Siemens Energy



a message to our industry from ...

Electric Machinery
Committee Task Force



"Coordination of Grid Codes and Generator Standards: Consequences of Diverse Grid Code Requirements on Synchronous Machine Design and Standards"



- IEEE Task Force
 Members include
 Generator Owners,
 Manufacturers, TSOs,
 Regulators &
 Consultants, ...
- ... who are to prepare a report recommending improvements and harmonisations to:
 - 1. Generator Standards
 IEC60034 & IEEE C50.13.
 - 2. Grid Codes

	Bob	Cummings	Lon	Montgomery
	Bob	Gray	Luis	Rouco
	Carsten	Zuehlke	Marc	Zeidman
	Changtai	Xu	Markus	Egretzberger
	Chavdar	Ivanov	Matthias	Baechle
	Edson	Bortoni	Michel	Rioual
	Evert	Agneholm	Mike	Sedlak
	Geoff	Klempner	Nico	Smit
	Hirohide	Murayama	Nils	Nilsson
	Izzy	Kersenbaum	Pierre	Ouellette
	Jason	Kapelina	Randall	Groves
	Jim	Lau	Raul	Rico
	Jim	Michalec	Relu	Ilie
	Joe	Hurley	Robert	Thornton-Jones
	John	Yagielski	Ruediger	Kutzner
	Kay	Chen	Ryan	Quint
	Kenichi	Hattori	Satoshi	Mizukami
	Kevin	Chan	Steve	Richards
	Kevin	Mayor	Thong	Vu Van
	Leo	Lima	Uwe	Seeger
	Les	Hajagos	William	Bloethe



CONCLUSION:

Cigré, IEC & IEEE must cooperatively pursue describing required attributes of desired operational flexibility ... to include:

- duty cycles (start-stops, MW-MVAR load cycles)
- weighted average efficiency

operational flexibility 14 25.Oct.2016 Page 4



Operational Flexibility Attributes being discussed:

- Voltage-frequency operating ranges and durations
- Reactive power capability
- Generator short-circuit ratio (SCR)
- > Rate of Change of Frequency (RoCoF) withstand capability
- > Fault ride through
- Excitation voltage ceiling factor
- > Auto-reclosing
- Power output as function of frequency

operational flexibility 14 25.Oct.2016 Page 5



Operational Flexibility Attributes being discussed:

- Voltage-frequency operating ranges and durations
- Reactive power capability
- Generator short-circuit ratio (SCR)
- > Rate of Change of Frequency (RoCoF) withstand capability
- > Fault ride through
- Excitation voltage ceiling factor
- > Auto-reclosing
- Power output as function of frequency

See presentations by Luis Rouco & John Yagielski



Operational Flexibility Attributes being discussed:

- Voltage-frequency operating ranges and durations
- Reactive power capability
- Generator short-circuit ratio (SCR)
- Rate of Change of Frequency (RoCor
- Fault ride through
- Excitation voltage ceiling
- > Auto-reclosing
- Power output as function
- >duty cycles
- weighted average efficiency

pability




Operational Flexibility Attributes being discussed:

>duty cycles


Page 8







Changing speed & MW-MVAR in typical daily grid demand profile



- Several start-stops / day & week depending on renewable energy production
- Fast & frequent steps in MW to balance weather dependent renewable energy
- Continuous MVAR variation to stabilize fluctuating grid conditions

provided by Siemens Energy, Inc.



Excerpt about duty cycles from IEC 60034-1 ...

4.1 Declaration of duty


It is the responsibility of the purchaser to declare the duty. The purchaser may describe the duty by one of the following:

- a) numerically, where the load does not vary or where it varies in a known manner
- b) as a time sequence graph of the variable quantities
- c) by selecting one of the duty types S1 to S10 that is no less onerous than the expected duty.



Excerpt about duty cycles from IEC 60034-1 ...

c) by selecting one of the duty types S1 to S10 that is no less onerous than the expected duty






Excerpt about duty cycles from IEC 60034-1 ...

Where the purchaser does not declare a duty, the manufacturer shall assume that duty type S1 (continuous


running duty) applies.






Excerpt about duty cycles from IEC 60034-1 ...

b) as a time sequence graph of the variable quantities perhaps something like this





Changing speed & MW-MVAR in typical daily grid demand profile



- Several start-stops / day & week depending on renewable energy production
- Fast & frequent steps in MW to balance weather dependent renewable energy
- Continuous MVAR variation to stabilize fluctuating grid conditions

provided by Siemens Energy, Inc.




Operational Flexibility Attributes being discussed:

>weighted average efficiency

operational flexibility 14 25.Oct.2016 Page 16





provided by Siemens Energy, Inc.

- · High number of start-stop cycles
- Operation in whole released capability range (& infrequently at rated load)
- High share of reactive power for grid stabilization
- Full use of under-excitation capability because of capacitive grid demands


Increased demand on highly flexible load operation of conventional power plants



Possibility for flexible operation to increase efficiency:


- Variable operation with fixed H2 over-pressure
- Variable operation with varied H2 over-pressure

Iower part load losses with varied H2 overpressure





Weighted average efficiency with fixed H2 overpressure




= 99.08% weighted average efficiency

Siemens Energy, Inc.




Weighted average efficiency with fixed H2 overpressure



Energy, Inc.



Weighted average efficiency with varied H2 overpressure




provided by Siemens Energy, Inc.

= 99.17% weighted average efficiency



Consider: Amend turbogenerator standards to allow specification of several operating points at which efficiency is to be quoted, with % weightings for each point by agreement



fixed H2 pressure @ 75 psig: 99.06% weighted average efficiency

varied H2 pressure@ 75 - 5 psig: 99.17% weighted average efficiency

0 200

400 6

600 80

800 10


1200 1

operational flexibility 14 25.Oct.2016

Page 22



Consider: Amend turbogenerator standards to allow specification of several operating points at which efficiency is to be quoted, with % weightings for each point by agreement



fixed H2 pressure @ 75 psig: 99.06% weighted average efficiency

varied H2 pressure@ 75 - 5 psig: 99.17% weighted average efficiency

≈ 800 kW green difference

200 400

0 800

1000 1200

1200 14 Page 23



CONCLUSION:

Cigré, IEC & IEEE must cooperatively pursue describing required attributes of desired operational flexibility ... to include:

- duty cycles (start-stops, MW-MVAR load cycles)
- weighted average efficiency

operational flexibility 14 25.Oct.2016 Page 24